



202 (COMMERCIAL AUDIO SOLUTIONS



PROFESSIONAL AUDIO OVER IP SOLUTIONS



MONACOR-DT, shaping up for the future ...

Thanks to the new DT series, Audio over IP solutions with Dante® interfaces can now conveniently be implemented at a very attractive price. Taking centre stage is the speaker **WALL-05DT**.



Dante

Audinate®, the Audinate logo and Dante® are trademarks of Audinate Pty Ltd.

Contents

	Know-how on 100 V PA Technology 2 Know-how on Audio over IP 4 Services offered by MONACOR 6	
DIY Store, Flush-mount Speakers and Surface-mount Speakers	Petrol Station, Surface-mount Speakers	10
	Church, Surface-mount Speakers 40 Mosque, Surface-mount Speakers 42	32
Campsite, Flush-mount Speakers and Surface-mount Speakers	Fitness Centre, Flush-mount Speakers and Surface-mount Speakers 58 Trampoline Park, Flush-mount Speakers and Surface-mount Speakers 60 Dental Practice, Flush-mount Speakers and Surface-mount Speakers 62 Retirement Home, Flush-mount Speakers 64 Sports and Leisure Centre, Flush-mount Speakers and Surface-mount Speakers 66	44
Restaurant, Flush-mount Speakers and Surface-mount Speakers	Café, Flush-mount Speakers	68
Office Buildings, Surface-mount Speakers	Seminar Room, Flush-mount Speakers 88 Seminar Room, Surface-mount Speakers 90 Conference Room, Surface-mount Speakers 92	82
	MONACOR Project Support94	

Know-how on 100 V PA Technology

Pleasant background music in restaurants, unobtrusive advertising in supermarkets or a clearly understandable presentation at conferences and conventions; comprehensive professional PA technology can be used for various applications in the public and commercial sector. The great variety of PA systems also requires a wide range of products. As specific as requirements may be, our extensive product range will certainly provide you with the right solution for your project.

This solutions brochure will show you various PA applications and gives useful information and advice in order to facilitate your decision, depending on the range of application. With numerous illustrative examples of application, the MONACOR product portfolio offers practicable solutions for versatile applications. The scenarios in this brochure can certainly provide you with further ideas and practice-oriented information for your own application. In any case, you will find out how complex this topic is which is influenced by numerous factors and requires comprehensive planning.

No matter whether buildings, sports facilities or wide open spaces, quite specific requirements are made on PA systems used for the reproduction of speech and music. This is the perfect application for 100 V PA technology.

With professional 100 V technology, the audio signal is transformed up and then down again at the speaker. Thus, it is possible to achieve a consistent and continuous sound radiation without the risk of performance loss when transmitting signals over greater distances, for example. Other advantages: the small cable cross section reduces cabling effort, facilitates installation and also goes easy on your budget.

PA audio installations normally supply a mono signal (mono = sum L+R). In contrast to a hi-fi stereo system as we know from applications at home, the PA technology is mainly directed towards an audience which moves freely in a room and ought to hear the complete information at any position. However, stereo reception would be the first choice for an audience which is always at an equal distance to the speakers, e.g. when sitting on the sofa at home.


A permanently installed PA system for consistent radiation of background music, announcements or for emergency announcements is suitable for most versatile applications:

- Supermarkets, department stores and shops
- Hotels and restaurants
- Sports fields and gyms
- Schools, universities and other educational institutions
- Office buildings, industrial buildings and warehouses
- Churches, chapels and mosques
- Cultural facilities, including museums or art galleries

In case, you are planning a more complex PA system with speaker distribution in several rooms, this can quickly result in long cable paths. Lengths of 100 m and more are quite common between audio source and speakers. Additionally, you may also want to adjust the volume individually for each room and have the facility to switch off the background music or disable announcements in certain rooms. For the specific application in a doctor's practice, this would mean that ...

- ... pleasant and unobtrusive background music should be played in the hallway and waiting area,
- ... a CD or MP3 file should be played in the treatment rooms and
- ... announcements from the reception should be heard in the hallway, waiting area and treatment rooms. The volume of the currently playing music will be lowered and priority is given to the announcement.

This example shows: all areas in a 4-zone solution can individually be supplied with high-quality music. An absolutely user-friendly operation, a top-quality sound and excellent speech intelligibility turn this audio solution into a high-performance PA system. This is only one of many examples. We have prepared a few more on the following pages.





Know-how on Audio over IP

100 V PA technology has been used as standard in the field of fixed PA installations for a long time now. In the digital age, however, requirements made on PA applications are constantly changing. Buildings should be smarter, cables almost invisible and speakers preferably be controlled from one central control panel. In fact, most digital mixers already feature a network interface. This means that Audio over IP solutions become more and more important, even on stage where analogue systems have dominated the scene so far. They also become increasingly easier to operate and are available at a more and more attractive price.

What does AoIP mean? And what are the benefits?

AoIP stands for Audio over Internet Protocol and is a solution for transmitting digital audio signals via IP network (usually a Local Area Network = LAN). The sound is divided into little digital packets and then transmitted to its destination using the network infrastructure. The IP address ensures that each audio packet is sent to the correct destination (usually a speaker), even when several different destinations are used (multiple speakers). The receiving station must be able to unzip the audio packets and assign them accordingly.

The audio signal uses the same connection as all other data in the network: mails, backups, merchandise management system, all Internet traffic. Separate leads for announcements and background music are not required. In addition, this technology ensures a high level of flexibility during planning and implementation. Thus, cost-effective Ethernet cabling can be applied instead of heavy and often very expensive analogue cables or multicore cables. Above all, AoIP provides the user with more freedom:

- With an AoIP solution, you are able to distribute audio signals as required. You can address and configure each speaker individually. Depending on the transmission system, it is possible to display all speakers used in one room on the PC using a routing matrix. For a mutual communication, you only require a connection to the IP network.
- Audio components are connected via the network, signals distributed via virtual link.
- When there are only small data packets left of the audio data, the emphasis is no longer put on the cable quality. The only thing that matters here is the data quality. Depending on the adjusted sampling rate, the data will be transmitted as produced without any further compression.

Live concerts, recording studios, broadcasting, live debates or large sound installations mean that higher requirements are made on the transmission speed, real-time capability and operating reliability of the network. For these applications, a network protocol is used which is specialised for audio transmissions: Dante[®].


Real-time Audio Networks

Dante® is the next step in digital audio networks and stands for Digital Audio Network Through Ethernet. You can particularly benefit from Dante® solutions when signals have to be transmitted over a great distance, e.g. for fixed installations in shops, hotels, restaurants, schools or indoor sports facilities. It is possible to transmit uncompressed and synchronised audio signals with virtually no latency. Dante® can be used in parallel to an existing network which makes it a particularly attractive option. With digital transmissions, there is no interference from other electrical devices and greater cable distances are possible without degrading the quality of the signal. The three most important components for Audio over IP transmission with Dante® interface are:

- Hardware modules: speakers, amplifiers, switches, speaker management systems
- The network protocol itself: the network protocol is the digital method to define rules, syntax and encryption according to which data packages are transmitted between hardware and software.
- The Dante® controller as control software: with the free software 'Dante® Controller', it is possible to determine from which specified Dante®-enabled device to which other specified Dante®-enabled receiver the audio signal is to be routed through the network. Sampling rates can be adjusted as required: the user can replay speech in a lower quality and music in a higher quality. Source and audio device have to feature the same sampling rate.

With network-enabled speakers and IP amplifiers from MONACOR, you will certainly find the perfect solution for every requirement. Reliable, easy and convenient operation: thanks to Dante® standards and the DT portfolio, the sky is the limit when it comes to possibilities.





Services offered by MONACOR: your advantage for making your project a success

You can take our word for it: as your point of contact, we are available for your questions and support — your call will not be forwarded to anonymous call centres, you will reach someone you know. We understand your request, may even know each other for some time now. In any case, we will help you with all of our experience and expert advice. You will benefit from our special service which includes personal contact, a fast response and reliable solutions. As our partner, you will also benefit from additional advantages:



3-year warranty is our promise of quality!

Our customers deserve highest reliability. In order to ensure this, we give a three-year warranty which also applies to all of our own-brand products. Extensive examination of the products and our detailed instruction manuals result in high standards and a high quality.







Brand advertising for your success

With targeted PR and marketing activities, we will strengthen user confidence in PA technology from the brand MONACOR. Thus, for example, product tests are thoroughly prepared and campaigns for online advertising or specialised magazines specifically planned and implemented. And we will always have an open ear for your advertising campaigns and provide support during implementation.


Everything at a glance

On more than 150 pages, we will show you our versatile range of PA products. An impressive selection of wall speakers, ceiling speakers and flush-mount speakers, voice alarm systems with EN 54 certification or mobile amplifier systems for professional fixed installations and sound applications — this catalogue from MONACOR offers a comprehensive range of products to fully meet your requirements.

Come and have a look at www.monacor.com and order your very own copy of the catalogue.

Our webshop – order quickly and easily online

Use this 24/7 service to search, find and order our latest technology — there are no limited opening hours. Set up your own customer account and take advantage from a highly convenient operation. You can take your time and have the opportunity to establish your requirements. You can easily identify availability, outstanding orders or arrears.







Always keeping you informed

With our regular newsletter, you will never again miss any news on PA technology from MONACOR. New products, useful practical tips and the latest news in the field — sent to you directly via e-mail.

Interesting articles, innovations as well as information on current events can also be found on our social media channels. Short, precise and exactly to the point — our video clips show you the most important product advantages and answer frequently asked questions regarding our product range.

Rely on our ability to deliver and benefit from a head start ...

Our storage area of 9,800 m² and a quick response to customer enquiries both ensure a high ability to deliver. If you place your order for delivery within Germany, goods will be delivered to you within 48 hours. The only thing even faster is our 24-hour Express Service for deliveries within Germany. You can choose the delivery date at your convenience.

Our quality requirements ensure highest operating reliability and a long service life

When it comes to quality, we leave nothing to chance and rely on our own strengths. Our proactive quality policy ensures most reliable products. Accredited test laboratories assist us with extensive and documented quality assurance tests as well as with tight tolerance limits. Thus, you will benefit from high quality standards — for all of our products.



Our product managers keep an open eye on the market and on future trends

Technology develops at a speed which can surely be described as breathtaking. Our product experts travel worldwide to uncover latest trends and developments in order to offer you the latest in technology. That provides you with a solid foundation for trendsetting systems which feature a reliable operation you can surely benefit from. The product management at MONACOR: market-oriented, innovative and inspirational.



Reliable, quick and without red tape – processing your order and dispatch handling

Customer comments confirm that they value our strong performance with regard to ability to deliver and processing of the orders which is a solid foundation for a good business relationship with us. Another advantage: our ability to deliver allows you to choose an exact delivery date.



Always available to assist

Our technical customer service department with highly qualified staff is an inherent part of our service provided. Your advantage: consistent points of contact, a spare parts store offering almost any part required and our technical archive. Thus, fastest response and processing times are guaranteed which are fundamentally important to us.





Solutions for Trade and Services

Supermarket

Flush-mount speakers 1,500–1,900 m²

Customer requirements:

- PA application with quiet and pleasant background music
- Microphone announcements with excellent speech intelligibility
- Four separate PA zones for individual voice transmissions and music reproductions
- Media streaming via LAN and WLAN
- Reproduction of (Internet) radio or MP3 files



PA ceiling speakers EDL-10TW/WS provide high-quality sound with a consistent radiation and are therefore perfectly suitable for reproduction of music and speech in supermarkets. The 4-zone mono mixing amplifier PA-40120 allows you to set up a multi-zone system for an independent PA application in the sales area, storage area and sanitary facilities. For music reproductions, the audio player WAP-200 features an integrated FM and DAB+ tuner as well as an integrated Internet radio. Microphone stations in the back office and in the checkout area allow for staff to easily make quick announcements to individual zones or all zones.

Products for this scenario:

38 x

EDL-10TW/WS

Order No. 0163380

PA ceiling speaker with integrated tweeter



1 x

PA-40120

Order No. 0173220

4-zone mono mixing amplifier with 4 active 120 W outputs



1 x

WAP-200

Order No. 0387030

Internet radio, FM RDS and DAB+ tuner, MP3 player



6 x

PA-4000RC

Order No. 0236010

PA 4-zone paging desktop microphone



Supermarket

Flush-mount speakers 1,500-1,900 m²



Zone 1

Zone 2

Zone 3

Zone 4

DIY Store

Flush-mount speakers and surface-mount speakers 1,600–1,900 m²

Customer requirements:

- Comprehensive PA application of highest speech intelligibility for the sales area including outdoor area and staff rooms
- Timed reproduction of announcements or advertising messages
- Microphone stations for the customer service desk, the back office or the checkout area
- Announcement facility via telephone system with A/B interface (PBX)
- PA application to be selected for 6 zones (indoors, outdoors, staff rooms, etc.)
- Robust and weatherproof speakers for open areas outdoors

Solution

Modern ball speakers EDL-420/WS also master most challenging acoustic conditions and are the top choice when it comes to speech reproductions in large rooms with high ceilings. The full range speaker of high power capability provides highest speech intelligibility and a consistent radiation across the entire sales area. Extra robust and weatherproof sound projectors EDL-110/WS are used for the outdoor area. Flush-mount speakers EDL-68/WS are applied in sanitary facilities and changing rooms, thus ensuring a PA application across the entire area. Wall speakers ESP-70/WS which have been installed in the warehouse ensure optimum intelligibility of announcements. The mono mixing amplifier PA-6600 of high efficiency is a real multi-talent and can be used for most versatile applications and provides a power rating of 600 W. The insertion module PA-1120DMT which is integrated into the amplifier allows for time-controlled announcements, e.g. special offers or advertising messages. The microphone station PA-6000RC can be used for additional announcements to be made by staff at the customer service desk or the back office to reach individual zones or the entire DIY store. An additional three desktop microphones PA-4300PTT are located in the checkout area. The MAESTRO-1 allows for further announcements to be made by every telephone connected to the telephone system and also allows you to broadcast voice messages in MP3 format or WAV format.

Products for this scenario:



EDL-420/WS Order No. 0161880 PA ball speaker (IP44)



Order No. 0161930

Weatherproof PA wall and ceiling speaker



EDL-68/WS Order No. 0162340

PA ceiling speaker with special 2-step mounting



Order No. 0162120
PA wall speaker



PA-6600 Order No. 0172390 6-zone mono PA mixing amplifier



Order No. 0235370
PA zone paging desktop microphone

X

PA-1120DMT Order No. 0174580 Digital message and timer insertion



PA-4300PTT
Order No. 0230980
PA desktop microphone (push-to-talk)



MAESTRO-1 Order No. 0176250 PA telephone announcement adapter



Flush-mount speakers 90–150 m²

Customer requirements:

- Pleasant and well-balanced background music in the sales area
- Audio streaming from a Bluetooth-enabled smartphone or tablet PC
- User-friendly operation of the entire system
- Versatile connecting facilities for additional audio sources
- Flush-mount speakers of an appealing design, matching the shop interior

Solution

Flush-mount speakers SPE-254/WS provide excellent background music and a powerful sound. The stereo mixing amplifier SA-440/SW features a particularly user-friendly operating concept, is clearly arranged and provides extensive adjustment options for each input channel. The Bluetooth audio receiver WSA-10BT is applied for wireless audio streaming from a tablet PC or smartphone.

Products for this scenario:

2 x

SPE-254/WS

Order No. 0105510
Pair of PA ceiling speakers



1 x

SA-440/SW

Order No. 0253880

Universal stereo mixing amplifier, 100 W



1 x

WSA-10BT

Order No. 0255800

Bluetooth audio receiver



Flush-mount speakers 90–150 m²





Surface-mount speakers 90–150 m²

Customer requirements:

- Background music for a pleasant surrounding to promote sales, without being obtrusive
- Music reproduction of MP3 files via connected USB flash drive
- User-friendly operation, even for non-technical users



Solution

Speakers EUL-60/SW are perfectly integrated into the concept of the shop and provide a well-balanced sound for reproduction of pleasant and unobtrusive background music. For music reproductions, the mono PA mixing amplifier PA-312DMP features an integrated MP3 player with USB port for connecting a flash drive. With two components only, the system remains uncluttered and impresses with an easy yet highly reliable operation. The amplifier features additional connections for reproduction from various audio sources, e.g. audio players with radio function or streaming media via network.

Products for this scenario:

2 X EUL-60/SW

Order No. 0161170
Pair of universal PA speaker systems



1 x

PA-312DMP

Order No. 0172980

Mono PA mixing amplifier with integrated MP3 player



Surface-mount speakers 90–150 m²





Flush-mount speakers 150–210 m²

Customer requirements:

- Speakers with a high-quality sound yet unobtrusive appearance
- Excellent reproduction of background music, even at higher volume levels
- Audio streaming via smartphone, tablet PC or stationary PC/Mac
- User-friendly and intuitive operation



Solution

Flush-mount ceiling speakers EDL-62HQ feature a flush fit protective metal grille which is magnetically attached to the speaker front. Thus, they can perfectly be integrated into the surrounding area - ideally suited for unobtrusive indoor PA applications without having to compromise when it comes to the sound quality. The 2-way version provides a wide frequency range and high-quality music. Your own smartphone, a tablet PC or a stationary PC/Mac can be used as an audio player. The WSA-50WIFI of particularly compact size receives audio signals and then transmits them to the mono mixing amplifier PA-924 via cable using the WLAN network.

Products for this scenario:

6 x

EDL-62HQ

Order No. 0163430
PA hi-fi wall and ceiling speaker, 30 W



1 x

PA-924

Order No. 0175060 Mono PA mixing amplifier



1 X WSA-50WIFI

Order No. 0257160
WLAN audio receiver



Flush-mount speakers 150–210 m²





Surface-mount speakers 130-210 m²

Customer requirements:

- Excellent sound characteristics for reproduction of background music
- Speakers which can perfectly be integrated into the shop interior
- Versatile audio sources for music reproduction: radio, MP3 files or CD
- Straightforward operation and highest reliability with perfect functionality

Solution

2-way speakers EUL-80/SW provide a crystal-clear sound at any volume level. These speakers are real eye-catchers in the sales area due to their modern and innovative design. The mono mixing amplifier PA-8120RCD with integrated CD/MP3 player and radio provides most versatile playback options and perfectly meets all requirements. Each component delivers exceptional fidelity and combines a comprehensive PA application with an extremely easy and intuitive operation.

Products for this scenario:

2 x

EUL-80/SW Order No. 0161190

Pair of universal PA speaker systems



1 x

PA-8120RCD

Order No. 0173040

Mono PA mixing amplifier with integrated CD/MP3 player and radio



Surface-mount speakers 130-210 m²





Petrol Station

Surface-mount speakers 80–130 m²

Customer requirements:

- PA application with unobtrusive and high-quality background music throughout the sales area
- Compact and easy-to-use system, even for untrained staff
- Music reproduction via FM radio or of MP3 files via USB/SD interface
- Wireless connection facility of Bluetooth-enabled devices, e.g. smartphone or tablet PC



Solution

For a continuous PA application throughout the petrol station shop, we have used the PA speaker systems ESP-215/WS. The 2-way system with 5 power taps ensures an optimum sound distribution throughout the entire sales area and ensures a reliable reproduction of both low and high frequencies. The speakers are driven by mono class D mixing amplifier PA-806DMP with a power rating of 60 W. Despite compact dimensions, the device combines wireless and cable-connected connection facilities with an impressive power capability and an easy operation. Extra high efficiency of the class D technology ensures minimum power consumption, improved heat generation and highest efficiency. Thanks to an integrated Bluetooth interface, wireless audio streaming from your music libraries onto a smartphone, tablet or laptop can easily be realised. Standard features also include an FM radio and media player for memory cards or USB flash drives.

Products for this scenario:

3 x

ESP-215/WS

Order No. 0199990 Weatherproof PA speaker system



1 x

PA-806DMP

Order No. 0176920

Mono class D PA mixing amplifier with integrated MP3 player, FM tuner and Bluetooth



Petrol Station Surface-mount speakers 80-130 m²



Hairdresser's

Surface-mount speakers 80–120 m²

Customer requirements:

- High-quality background music for the entire hairdressing salon
- Intuitive operation of the PA system
- Versatile audio sources for music reproduction
- To use a smartphone, tablet PC or PC as an audio player
- Bluetooth support for music reproduction via mobile devices



Solution

Pleasant background music in a hairdressing salon is to create a positive mood among customers. In addition to expert advice, this is an important part of the services offered. Thus, the applied PA system is very important. A total of 4 high-performance PA speaker systems MKS-248/WS provide perfectly balanced background music. Each of the 2-way bass-reflex speaker systems features 2 x 10 cm polypropylene bass-midrange speaker and a high-quality dome tweeter. The pivoting and tilting wall bracket facilitates easy installation and allows for flexible alignment. A hi-fi multi-room amplifier IWA-50WIFI/WS provides music to all 4 wall speakers. The elegant flush-mounted wall amplifier requires little space only, yet offers versatile features for a convenient operation. It supports audio sources via Wi-Fi, Bluetooth and AUX connection. Thus, audio players like smartphones, tablet PCs or PCs with DLNA-compatible software are suitable for music reproduction. The integrated 3.5 mm input allows for the class D amplifier with 2 x 25 W to turn into a music system for MP3 players or wired audio signals (e.g. CD player).

Products for this scenario:

2 x

MKS-248/WS

Order No. 0132050 Pair of 2-way wall-mount design speaker systems, 60 W, 8 Ω



1 x

IWA-50WIFI/WS

Order No. 0179020

Hi-fi multi-room amplifier with Wi-Fi and Bluetooth



Hairdresser's

Surface-mount speakers 80–120 m²



Car Dealership

Flush-mount speakers and surface-mount speakers 900-1,300 m²

Customer requirements:

- Flexible multi-zone system for various areas of application
- Comprehensive music and speech reproduction for 8 zones
- Elegant design speakers with a powerful sound for the showroom
- Excellent speech intelligibility in each area of the building, including the high entrance hall
- Weatherproof speakers for the outside display area
- Announcement facility at the reception, either to one zone or multiple zones
- Music reproduction via (Internet) radio, CD, MP3 player or via Bluetooth

Solution

High-quality 2-way column speakers are used for the PA application in the indoor and outdoor display areas. In the showroom, speakers ETS-8060TW/WS with a stylish aluminium cabinet are unobtrusively integrated into the building complex. Weatherproof and IP66 certified column speakers ETS-8100TW/ SW are used for the outdoor installation. Both models are suitable for speech and music reproduction and thanks to the flexible wall bracket, they can be perfectly aligned to the area of application. Mono power amplifiers PA-912S (1 x 120 W) and PA-948S (1 x 480 W) provide the necessary power. The other areas also feature a reliable PA application. Ceiling speakers EDL-118TW are installed into adjoining rooms and offices; the workshop features speakers WALL-06T/SW for a perfect audio reproduction. Sufficient power for both speaker series is ensured via the 8-channel class D amplifier PA-1850D (8 x 50 W) and one mono power amplifier PA-924S. Centrepiece of the whole PA system is the audio matrix DRM-884 which is able to easily meet the requirements of a multi-room installation with 8 zones. Users can combine signal sources, play one source in several zones or several sources in one zone and adjust the volume in each zone. The zone paging microphone DRM-884RC allows to make announcements to any zone required. Audio players WAP-200 and CD-112/BT are used for music reproductions.

Products for this scenario:



ETS-8100TW/SW

Order No. 0163790 High-quality weatherproof PA column speaker, IP66



EDL-118TW

Order No. 0163850 PA ceiling speaker with integrated tweeter



ETS-8060TW/WS

Order No. 0163780 PA hi-fi column speaker



WALL-06T/SW

Order No. 0163600 Pair of 2-way PA speaker



WALL-05T/WS

Order No. 0163590 Pair of 2-way PA speaker systems



PA-948S

Order No. 0177020 Mono PA power amplifier. 480 W



PA-924S

Order No. 0177010 Mono PA power amplifier. 240 W



PA-912S

Order No. 0177000 Mono PA power amplifier. 120 W



PA-1850D

Order No. 0172960 8-channel class D PA amplifier



WAP-200

Order No. 0387030 Internet radio, FM RDS and DAB+ tuner, MP3 player



CD-112/BT

Order No. 0212940

CD and MP3 player with Bluetooth receiver, USB interface and SD/MMC card slot



DRM-884

Order No. 0176940 Audio matrix router



DRM-884RC

Order No. 0176990 PA zone paging microphone for DRM-884



DRM-884VP

Order No. 0176980

Wall module for volume control of DRM-884

Car Dealership





Zone 1

Zone 2

Zone 3

Zone 4

Zone 5

Zone 6

Zone 7

Zone 8

Shopping Mall

Flush-mount speakers and surface-mount speakers 1,200–1,600 m²

Customer requirements:

- A clear and natural music reproduction in all areas of the shopping centre, e.g. shops, hallways and sanitary facilities
- PA applications to provide announcements of highest speech intelligibility for advertising purposes and for giving information on upcoming events
- Quick and easy operation of the system in order to fully concentrate on customer service
- Compact and unobtrusive flush-mount ceiling speakers which can easily be integrated into the shop interior
- Reliable technology which has extensively been developed for full-time operation



An excellent sound quality and speech intelligibility, a high operating range and a comprehensive PA application are crucial factors for rooms of high acoustic requirements.

The digital audio signals are directed from the centre management's back office to a total of four zones. It is possible to provide each zone with an independent PA application, selecting a different playlist and volume level via shuttle PC with pre-installed music software. Furthermore, it is possible to add tailor-made programs to the playlists to broadcast information or advertising and, if required, to allow for time-controlled playback. Dante[®]-enabled amplifiers PA-900DT and AKB-160DT have been applied in the shops. As Dante® instreamers, they receive a digital audio signal via an existing local network and feed it into the on-site audio system. The installed ceiling speakers EDL-62HQ provide a pleasant ambience at the point of sale. In the remaining areas, the installed active wall and ceiling speakers also guarantee a continuous PA application and feature an integrated 30 W amplifier as well as support Power over Ethernet to ensure a power supply via a connected PoE switch. Both the ceiling speakers EDL-80DT and the column speakers ETS-630DT can be addressed selectively (IP) and can stream high-quality multicast audio data. Each speaker can subsequently be assigned

to groups and zones without changing hardware or cabling.

Products for this scenario:

32 x

EDL-62HQ

Order No. 0163430

PA hi-fi wall and ceiling speaker, 30 W



8)

ETS-630DT Order No. 0163490

Active PA column speaker with Dante® module



6 x

EDL-80DT

Order No. 0163480

Active 2-way flush-mount ceiling speaker with integrated Dante® module





PA-900DT

Order No. 0176080

Mono PA mixing amplifier with integrated Dante® module

2 x

AKB-160DT

Order No. 0176070

PA amplifier module with integrated Dante® module



1 x

BMS-ZONE4

Order No. 0176190

Shuttle computer with ROSI BMS software, 4 channels, 2,600 tracks, including Dante® Virtual Soundcard licence



Shopping Mall

Flush-mount speakers and surface-mount speakers



















Solutions for Education and Houses of Worship

School

Surface-mount speakers 1,600-1,900 m²

Customer requirements:

- High speech intelligibility and clear announcements throughout the school premises
- Setting up of versatile call groups for specific information or intended elimination of certain areas which should not be disturbed
- Bell for recess is to be transmitted in each building complex
- Powerful PA application in the assembly hall for different kinds of events, e.g. school parties
- Most reliable operating safety due to 24 V emergency power supply in order to operate the system independently from the mains for a short period of time

Solution

For wide-ranging school premises, good speech intelligibility is top priority. We have used 2-way speakers WALL-05T/SW and WALL-04T/WS for the various rooms. The combination of bass-midrange speakers and dome tweeters ensures clear announcements. For the school's own gym, we have additionally used sound projectors RL-1EN and ball-proof speakers PAB-52WP/WS in order to guarantee a continuous PA application. A total of 3 microphone stations PA-6000RC can be used for making announcements into each zone individually or a selected number of zones. With the MAESTRO-1, it is also possible to make announcements via the telephone system. The power amplifier PA-2240 and a 6-zone mono mixing amplifier PA-6240 perfectly supply each of the PA zones. The digital message and timer insertion PA-1120DMT which is integrated into the amplifier allows you to create individual break signals and break times. In order to ensure announcements in case of an emergency, the system is connected to 24 V emergency power supply PA-24ESP. The PA system is complimented with a professional full range bass-reflex system for the assembly hall. Two professional full range bass-reflex speaker systems MOVE-12 (300 W) ensure an excellent sound reproduction and are ideally suited for smaller stages. The high-performance class D amplifier STA-1000DSP, preamplifiers PA-1414MX and the versatile CD and MP3 player CD-112/BT have also been added to the system.

Products for this scenario:



RL-1EN

Order No. 0163680

PA sound projector for wall mounting with EN 54-24 certification



WALL-05T/SW

Order No. 0163580 Pair of 2-way PA speaker



WALL-04T/WS

Order No. 0163570 Pair of 2-way PA speaker



PAB-52WP/WS

Order No. 0253580

Weatherproof highperformance PA speaker system, 50 W



MOVE-12

Order No. 0254920 Professional PA speaker system, 300 W, 8 Ω



PA-6240 Order No. 0172180

6-zone mono PA mixing amplifier



PA-1414MX

Order No. 0174770 10-channel PA preamplifier



PA-2240

Order No. 0170800 PA power amplifier



STA-1000DSP

Order No. 0255750 Stereo class D PA amplifier with DSP technology



PA-1120DMT Order No. 0174580

Digital message and timer insertion



CD-112/BT

Order No. 0212940

CD and MP3 player with Bluetooth receiver, USB interface and SD/MMC card slot



MAESTRO-1

Order No. 0176250

PA telephone announcement adapter



PA-6000RC

Order No. 0235370

PA zone paging desktop microphone



PA-24ESP

Order No. 0243120 24 V emergency power supply



PATL-100

Order No. 0171180

100 V transformer for connection of a 100 V audio signal source to devices with line input





NPA-12/24

Order No. 0280400

Rechargeable lead battery, 12 V. 24 Ah



Classroom

Surface-mount speakers 70–120 m²

Customer requirements:

- Well-balanced and consistent radiation with high speech intelligibility at every seating position in the room
- Laptop or computer to be used as an audio source
- Wireless audio transmission via Bluetooth
- Easy and straightforward operation, even for inexperienced users
- Compact and space-saving system



Solution

With PA speaker systems MKS-232/WS, it is possible to have a comprehensive PA application in the entire classroom. The 2-way speaker provide a high-quality sound which guarantees highest speech intelligibility at every seating position in the room. The compact and highly space-saving mini amplifier SA-160BT features an output of 60 W which is distributed onto 2 channels and allows for wireless streaming via Bluetooth. It is also possible for different users to operate the system thanks to the easy and intuitive operation of each component.

Products for this scenario:

1 x

MKS-232/WS Order No. 0132170

Pair of 2-way wall speakers, 30 W



1 x

SA-160BT

Order No. 0256010

Mini stereo amplifier, 2 x 30 W, with Bluetooth interface, NFC and remote control



Classroom

Surface-mount speakers 70–120 m²



Lecture Hall

Surface-mount speakers 220-400 m²

Customer requirements:

- PA application to cover the entire lecture hall as well as providing high speech intelligibility
- Excellent sound quality, even at higher volume levels
- Flexible and multifunctional use of the entire PA system
- Wireless media playback via laptop or other portable audio players
- Connection of a headband microphone for the speaker
- Barrier-free studying: an induction loop is transmitting the sound of the microphone directly to the hearing aid



Solution

High-end column speakers ETS-360TW/WS impress with an incredibly dynamic and complete sound, ensure highest speech intelligibility at any listening position and thus allow for attentive listening, even for several hours. Due to a precise sound radiation and a frequency range optimised for music, the column speaker ETS-360TW/WS is a speaker system which is suitable for versatile applications: for lectures, panel discussions as well as official parties with background music. It is also possible to establish a wireless connection between laptop and audio system via Bluetooth audio receiver WSA-10BT, if required. As the last step of signal amplification, preamplifier PA-1414MX and power amplifier PA-2240 ensure a perfect sound.

Large rooms, crowds of people, annoying ambient noise: these circumstances make attentive listening very difficult, particularly for the hearing impaired. In the lecture hall, hearing aids receive wireless audio signals via an installed induction loop which is driven by active loop amplifier LA-402.

Products for this scenario



ETS-360TW/WS

Order No. 0162270

High-end column speakers in a wooden cabinet of compact size



PA-1414MX

Order No. 0174770 10-channel PA preamplifier



PA-2240

Order No. 0170800 PA power amplifier





LA-402

Order No. 0179160

Active loop amplifier for rooms up to



WSA-10BT

Order No. 0255800 Bluetooth audio receiver



TXA-802SR

Order No. 0172990

2-channel multifrequency receiver



TXA-800HSE Order No. 0172250

Multifrequency pocket transmitter






TXA-800PS

Order No. 0252140 Intelligent PWM guick-charge station



Lecture Hall

Surface-mount speakers 220–400 m²





Church

Surface-mount speakers 950-1,300 m²

Customer requirements:

- High-quality sound and music reproduction
- Consistent sound radiation, even in difficult acoustic conditions
- Frequency-stable radiation of each speaker
- Hearing assistance directly to hearing aids or inductive receivers through magnetic induction
- Versatile use, e.g. for church service, concert or theatrical performance



Solution

PA column speakers ETS-120SL/WS and ETS-220TW/WS provide the perfect sound in a challenging acoustic environment. The slimline design allows for an architecturally unobtrusive installation. No matter whether you are sitting in the first row or last row, the speakers deliver a clear and precise reproduction of speech and music without any acoustic feedback. The splitter PA-24AD is used to route the signals to the 120 W mono mixing amplifier PA-900S as well as the class D amplifier STA-850D. For the inductive transmission of speech and music, we have applied loop amplifier LA-202. The inductive receiver LR-202 then receives the electromagnetic field which is created by an induction loop and converts it into an audio signal for the audience. The CD-112/BT is used as an audio player which can play both CDs and MP3 files and features an integrated Bluetooth receiver.

Products for this scenario:

ETS-120SL/WS

Order No. 0163450 Pair of line array design speakers in slimline extruded aluminium cabinets



PA-1414MX Order No. 0174770

10-channel PA preamplifier



PA-900S

Order No. 0172080

Mono PA power amplifier



STA-850D

Order No. 0252360 8-channel class D amplifier



PA-24AD

Order No. 0171890 10-way PA line splitter



CD-112/BT

Order No. 0212940

CD and MP3 player with Bluetooth receiver, USB interface and SD/MMC card slot



LA-202

Order No. 0176360 Active loop amplifier



LR-202

Order No. 0176370 Inductive receiver






ECM-310P Order No. 0232430

PA desktop microphone with gooseneck

Church

Surface-mount speakers 950–1,300 m²



Mosque

Surface-mount speakers 270–420 m²

Customer requirements:

- Speech reproduction for acoustic amplification, e.g. of prayers or sermons
- Natural sound and high speech intelligibility throughout the entire mosque, despite challenging and difficult room acoustics
- Elegant speakers for an unobtrusive integration into the existing architecture
- Versatile audio player for playback of the Quran and for recording prayers and sermons
- Hearing assistance directly to hearing aids or inductive receivers through magnetic induction



Column speakers ETS-120SL/WS and ETS-220TW/WS are of an elegant and unobtrusive design and thus can perfectly be integrated into the architecture of a mosque. Despite their unobtrusive appearance, you don't have to miss out when it comes to sound quality. There are no unwanted reflections from walls or ceilings because the sound energy is emitted directly towards the audience. The PA-24AD distributes the signal to the connected mono class D power amplifier PA-1250D and the class D amplifier STA-450D. The signal is transmitted to the inductive receiver LR-202 via loop amplifier LA-202 using electromagnetic induction. The DPR-110 is used for audio reproductions and features a USB interface and an SD/MMC card slot. A recording feature completes the range of functions.

Products for this scenario:

2 x

ETS-120SL/WS

Order No. 0163450
Pair of line array design
speakers in slimline extruded
aluminium cabinets





1)

PA-1414MX

Order No. 0174770 10-channel PA preamplifier



X

PA-1250D

Order No. 0173860 Mono class D PA power amplifier



 $1 \times$

STA-450D

Order No. 0252350 4-channel class D amplifier



PA-24AD

Order No. 0171890 10-way PA line splitter



DPR-110

Order No. 0212320
MP3 recorder with USB interface and SD/
MMC card slot



I X

LA-202

Order No. 0176360 Active loop amplifier



Order No. 0176370 Inductive receiver



TXA-802SR Order No. 0172990

2-channel multifrequency receiver



1 X

TXA-800HT

Order No. 0172260

Hand-held microphone with integrated multifrequency transmitter



Mosque

Surface-mount speakers 270–420 m²







Solutions for Leisure, Health Care and Residential Care

Football Pitch

Surface-mount speakers 7,200–10,500 m²

Customer requirements:

- Reliable and efficient all-round solution with a high sound pressure and top-quality audio reproduction, even for music with high volume levels
- Excellent speech intelligibility across the entire ground
- CD player for various audio players (incl. MP3 reproduction, FM/AM tuner and USB interface)
- Robust and weatherproof speakers for fixed installations at poles or the stands
- Microphone for announcements



The volume level of the audience at sporting events is a particular challenge for the applied PA technology. Weatherproof music horns IT-400TW with IP66 certification provide a powerful yet precise sound which ensures announcements to remain understandable. For a detailed music reproduction, the IT-400TW feature a dynamic cone bass-midrange speaker and horn tweeter which ensure a distinct bass volume. The audio player is connected to the high-performance mono mixing amplifier PA-948 with 480 W. The highly versatile CD and MP3 player CD-112RDS/BT features an integrated FM RDS tuner, USB interface as well as SD/MMC card slot and thus perfectly meets every requirement. A wireless connection to a laptop, smartphone or tablet PC can be established via the Bluetooth receiver. The PDM-302 is available for visitor information or commentating sporting events, etc.

Products for this scenario:

8 x

IT-400TW

Order No. 0162580 Weatherproof horn speaker (music horn), 2-way technology



1 x

PA-948

Order No. 0175070 Mono PA mixing amplifier



1 x

CD-112RDS/BT

Order No. 0212950

CD and MP3 player with FM RDS tuner and Bluetooth receiver



1 x

PDM-302

Order No. 0235560
PA desktop microphone with gooseneck





Campsite

Flush-mount speakers and surface-mount speakers 2,800–5,500 m²

Customer requirements:

- Robust and reliable PA system for announcements and instructions of the staff with a high speech intelligibility
- 6 separate PA sound zones, to be controlled individually
- Unobtrusive background music indoors, including restaurant and reception area
- Music reproduction via FM radio or DAB+
- High-quality weatherproof speaker systems in the outdoor area of the restaurant
- Zone paging microphone in the back office or at the reception
- Maximum operating safety due to 24 V emergency power supply

Solution

The PA system on a campsite is mainly required for voice reproductions. For the wide open area, we have used weatherproof horn speakers IT-40 with IP66 certification. Unobtrusive background music is additionally required for both the entrance area with an adjoining little restaurant and sanitary facilities of the main building. In the restaurant, we have used hi-fi ceiling speakers ESP-22/WS. The 2-way version (full range speaker with movable dome tweeter) ensures an excellent sound quality. In addition, we have also applied 2-way speaker systems ESP-232/SW with IP55 certification to provide a well-balanced and unobtrusive background music on the terrace of the restaurant. In the sanitary facilities, we have used compact flushmount speakers EDL-22/WS. All of the 4 speaker series are driven by mono mixing amplifier PA-6480 with a power rating of 480 W for up to 6 zones. A connected desktop microphone PA-4000PTT in the office or at the reception is used as a microphone station for making important announcements. It is also possible to play stored messages via digital message insertion module PA-1120DMT (time-controlled) which is integrated into the amplifier. If the operation is to be maintained during a power failure, connection to a 24 V emergency unit PA-24ESP is recommended. The music for the background is inserted via digital stereo tuner FM-102AB.

Products for this scenario



IT-40 Order No. 0161360 Weatherproof horn speaker



ESP-22/WSOrder No. 0161670
PA hi-fi wall and ceiling speaker



ESP-232/SW Order No. 0162600

Weatherproof 2-way PA wall-mount speaker system



EDL-22/WS Order No. 0162770 PA ceiling speaker



PA-6480 Order No. 0172190 6-zone mono PA mixing amplifier



1 2

PA-1120DMTOrder No. 0174580
Digital message and timer insertion



Order No. 0174490
Digital stereo tuner for reception of FM and DAB+



PA-4000PTT
Order No. 0236000
PA desktop microphone (push-to-talk)



PA-24ESP Order No. 0243120 24 V emergency power supply



NPA-12/24 Order No. 0280400 Rechargeable lead battery, 12 V, 24 Ah

Campsite

Flush-mount speakers and surface-mount speakers 2,800–5,500 m²



Escape Room

Flush-mount speakers and surface-mount speakers 220-310 m²

Customer requirements:

- Excellent sound quality of applied speaker systems, for both music and voice reproductions
- Continuous PA application for each room, including theme rooms, fover and sanitary facilities
- Different areas of operation require a flexible multi-zone control in order to route multiple audio signals to any output
- A microphone station has to be available in the control room for hints and clues from the game master

Solution

For hobby detectives or anyone who loves to solve riddles, escape room games are an excellent leisure activity. A small group of people have got an hour to find their way out of a locked room. Hidden clues and mysterious riddles must be solved using logical thinking, team spirit and creativity. A flexible multi-zone system is required to provide each room with different audio sources (miking as well as music). For the foyer as well as for sanitary facilities, we have applied ceiling speakers EDL-68/WS or EDL-22/WS. Theme rooms have been fitted with speaker systems EUL-60/SW. The 2-way bass-reflex system with 11 mm dome tweeter ensures a very high sound quality. The team can use boundary microphone ECM-302B to ask the team leader for help who communicates via zone paging microphone ARM-880RC. The team leader can also listen to each of the 3 theme rooms via additionally applied PA speaker EUL-75/WS in the control room. Furthermore, 2 dual CD and MP3 players CD-122 are available for an independent PA application in each of the 4 music zones. This is made possible via audio matrix router ARM-880 which allows you to route up to 8 audio sources to an equal number of zones. A wall module ARM-880WP2 is used for remote control. The class D amplifier PA-1850D (8 x 50 W) provides the voltage for the connected speaker series.

Products for this scenario:



EUL-60/SW Order No. 0161170 Pair of universal PA speaker systems



EDL-68/WS Order No. 0162340 PA ceiling speaker with special 2-step

EDL-22/WS Order No. 0162770 PA ceiling speaker



EUL-75/WS Order No. 0162500 PA speaker system



PA-1850D Order No. 0172960 8-channel class D PA amplifier



CD-122 Order No. 0212820 Dual CD and MP3 player with USB 2.0 interface and SD/MMC card slot



ARM-880 Order No. 0173800 Audio matrix router





Order No. 0173840 Wall module for remote control of audio matrix router ARM-880

ARM-880WP2



ECM-302B Order No. 0232370 Boundary microphone



Museum

Flush-mount speakers and surface-mount speakers 1,700-2,000 m²

Customer requirements:

- Unobtrusive music radiation which is to be controlled individually for foyer, restaurant and museum shop
- Announcement facility with paging function and priority circuit
- To reduce volume level of the background music automatically for announcements which are to be routed to a selected zone or all zones
- For the exhibits, compact external media players are available for reproduction of individual audio files
- Setting up an inductive sound system for wireless reception of audio signals
- Portable tour guide system which ensures unrestricted movement during guided tours of a museum

Solution

For the foyer, we have used 2-way pendant speakers EDL-435/WS. They provide background music with a homogeneous sound distribution. In addition, hi-fi speakers EDL-62HQ have been applied in the shop and restaurant, ceiling speakers EDL-84/WS in the sanitary facilities and flush-mount speakers EDL-25 in the exhibition area. Mono mixing amplifier PA-6480 with a power rating of 480 W is used for operating all of the passive speaker systems. It features 100 V outputs for a maximum of 6 PA zones with individual volume control. The insertion module PA-1200RDSU and zone paging microphone PA-6000RC complement the wide variety of applications possible with the amplifier. Any visitor wishing to have a spontaneous audio tour without prior notice can receive further information on the exhibits via insertion modules DMP-102. The loop amplifier LA-202 and inductive receiver LR-202 ensure wireless reception of the signal inserted into the inductive loop. Within the loop, any number of receivers can be operated which are available at the ticket counter, if required. At the same time, the electromagnetic audio signal sent via the ring loop can also be used via the T-coil of a hearing aid. In case of an announcement, it will be transmitted to the induction loop with highest priority and the running programme interrupted for the duration. Voice transmission system ATS-50T or ATS-50R is available for guided museum tours.

Products for this scenario:



EDL-25 Order No. 0161440 PA ceiling speaker



EDL-62HQ Order No. 0163430 PA hi-fi wall and ceiling speaker, 30 W



EDL-435/WS Order No. 0163460

High-quality 2-way PA pendant



EDL-84/WS

Order No. 0162350 PA ceiling speaker



PA-6480 Order No. 0172190

6-zone mono PA mixing amplifier



LA-202 Order No. 0176360 Active loop amplifier



LR-202 Order No. 0176370 Inductive receiver



DMP-102 Order No. 0177090

Compact MP3 player insertion module with USB interface and SD/MMC card slot



PA-1200RDSU Order No. 0175030

FM/AM RDS tuner insertion with USB interface



PA-6000RC Order No. 0235370

PA zone paging desktop microphone



ATS-50R Order No. 0255160

40-channel PLL receiver



ATS-50T Order No. 0255170

40-channel PLL transmitter for microphone operation and audio line signals



ATS-25C

Order No. 0255180

Transport bag with integrated charging function for transmitters and receivers of the ATS-50 series



PATL-100

Order No. 0171180

100 V transformer for connection of a 100 V audio signal source to devices with line input



Museum

Flush-mount speakers and surface-mount speakers













Indoor Riding Arena

Surface-mount speakers 800-1,200 m²

Customer requirements:

- Music reproduction with an excellent sound quality, e.g. for background music during dressage programs
- Versatile audio player for the reproduction of various audio sources
- Compact microphone with two-way communication for riding lessons
- Applied speakers to provide an excellent sound
- Robust speakers, insusceptible to dust, heat and moisture

Solution

Music horns IT-300TW have been used for a consistent sound radiation in an indoor riding arena. Regardless of whether used for basic riding lessons or at a competition, the 2-way technology allows for a high-quality music reproduction as well as meeting high musical standards. The speaker with IP66 certification is resistant to dust, heat and moisture and perfectly meets the challenging requirements of an indoor riding arena. Mono mixing amplifier PA-924 provides an output power of 1 x 240 W and features versatile connection facilities. Multi-purpose audio player CD-112RDS/BT is used for music reproduction and plays CDs as well as MP3 files and also features additional reproduction options via radio and Bluetooth.

With the digital voice transmission system ATS-22, riding lessons are going to be even easier: riders are provided with the extra lightweight receiver ATS-22R and an unobtrusive earphone. Instructions of the riding instructor are communicated via transmitter ATS-22T. The highlight: thanks to the two-way communication function, it is possible for the riding pupil to ask questions, too. Another advantage: hands-free operation allows for the instructor and rider to move freely within the operating range (up to 70 metres). A desktop microphone PDM-302 can be connected to the PA system for commentating riding competitions, for example.

Products for this scenario:



IT-300TW

Order No. 0162230

Weatherproof horn speaker (music horn),
2-way technology



|)

PA-924 Order No. 0175060 Mono PA mixing amplifier



1)

CD-112RDS/BT

Order No. 0212950

CD and MP3 player with FM RDS tuner and Bluetooth receiver



Order No. 0257110

16-channel miniature receiver



1 x

ATS-12CB Order No. 0255660

Transport bag with integrated charging function



PDM-302 Order No. 0235560

PA desktop microphone with gooseneck

Indoor Riding Arena

Surface-mount speakers 800-1,200 m²



Swimming Pool

Flush-mount speakers and surface-mount speakers 1,500-1,900 m²

Customer requirements:

- Excellent speech intelligibility for announcements made via the connected microphone
- High-quality music reproduction for training courses, e.g. aqua jogging
- Versatile playback options for background music, e.g. from CD or MP3 files
- Moisture-proof speakers, protected against high humidity

Solution

Speaker systems ESP-250/WS with 2-way system provide a consistent and high-quality sound radiation in the swimming pool area. Ceiling speakers EDL-158 ensure that announcements made are also clear and understandable in the changing rooms and in the entrance area. Matrix router ARM-880 is used for signal transmission and allows you to route up to eight different audio sources to an equal amount of speaker zones. With the connected zone-paging microphone ARM-880RC, you can make sure that announcements made are clear and understandable, either in certain zones or in every zone and, if required, with priority circuit. In order to allow for a reproduction of unobtrusive background music, audio player CD-112RDS/BT features a Bluetooth receiver for a wireless connection of laptops, smartphones or tablet PCs. It is of course also possible to reproduce CDs or MP3 files from USB storage media and SD/MMC cards. Power amplifier PA-4240 allows you to implement up to 4 speaker lines and is controlled via the audio output of the ARM-880.

Products for this scenario:



ESP-250/WS

Order No. 0162780

PA speaker system in a weatherproof, white plastic cabinet with protective aluminium grille



EDL-158

Order No. 0162930

Weatherproof PA ceiling speaker



PA-4240 Order No. 0170820 PA power amplifier



CD-112RDS/BT Order No. 0212950

CD and MP3 player with FM RDS tuner and Bluetooth receiver



ARM-880

Order No. 0173800 Audio matrix router



ARM-880RC

Order No. 0173810

PA zone paging microphone

Swimming Pool

Flush-mount speakers and surface-mount speakers













Fitness Centre

Flush-mount speakers and surface-mount speakers 520-840 m²

Customer requirements:

- Flexible and high-quality multi-zone solution for reproductions of music and speech
- Unobtrusive background music in the bar area as well as in the changing
- Excellent sound quality in the training room with a rich and powerful bass for a motivating environment during training sessions
- Versatile playback options for music reproductions in the entire fitness
- Optional: connection of a wireless microphone for sessions in the training

Solution

Flush-mount ceiling speakers EDL-10TW/WS provide pleasant background music in the entire fitness centre, including the training area, changing rooms and the lounge area. The 2-way speakers feature an excellent sound quality with a consistent radiation pattern and impress with a high-quality music reproduction. Power amplifier PA-4240 with 4 x 240 W drives the connected speakers and ensures a reliable operation. With the 2-zone mixer MPX-52PA, it is possible to implement 2 independent zones with versatile routing options for each input channel. The workout area is provided with a powerful music reproduction for a motivating training ambience, whereas the bar area and changing rooms should feature a pleasant and unobtrusive sound. Audio player WAP-200 offers versatile playback options, e.g. Internet radio, FM RDS and DAB+ tuner, MP3 player or audio streaming via network.

The PA application in the course room has to meet special requirements: various playback options, powerful sound with a powerful bass, easy-to-use system, easiest operation and highest reliability. Speakers EUL-2/SW with a high efficiency and 2 x 20 cm (8") bass speaker and a dynamic 25 mm horn tweeter combined with a subwoofer EUL-2SUB/SW provide a precise and clear sound for a deep and dynamic bass reproduction. The system also includes 4-channel microphone line mixer VMX-440/SW, power amplifier PA-2240 as well as CD-112/BT with CD and MP3 player.

Products for this scenario:



EDL-10TW/WS

Order No. 0163380

PA ceiling speaker with integrated tweeter



EUL-2/SW Order No. 0174450 PA speaker system



EUL-2SUB/SW Order No. 0174460 Subwoofer



PA-4240 Order No. 0170820

PA power amplifier



PA-2240 Order No. 0170800 PA power amplifier



MPX-52PA

Order No. 0202300

2-zone mixer for multi-room PA applications



VMX-440/SW Order No. 0202530

4-channel microphone line mixer



WAP-200

Order No. 0387030

Internet radio, FM RDS and DAB+ tuner. MP3 player



CD-112/BT


Order No. 0212940

CD and MP3 player with Bluetooth receiver, USB interface and SD/MMC card slot



Fitness Centre

Flush-mount speakers and surface-mount speakers 520-840 m²









Trampoline Park

Flush-mount speakers and surface-mount speakers 1,600–1,900 m²

Customer requirements:

- Continuous PA application throughout the entire hall, suitable for reproduction of music and speech
- Speakers applied in the trampoline areas to provide a high-quality sound and feature a high volume capability
- Background music in the restaurant area, changing rooms and sanitary facilities
- Various audio sources, including CD, USB storage media, SD/MMC cards and Bluetooth
- Microphone station for announcements to either all or selected areas of operation

Solution

The tried and tested speakers PAB-6WP/WS are used for the PA application of the large hall. A total of 8 high-performance PA speaker systems with a 2-way bass-reflex system provide the required sound quality and volume levels. They are driven by a high-performance mono amplifier PA-1960 which features a power rating of 960 W. In the restaurant area, speaker systems WALL-05T/SW deliver pleasant background music for the PA application. In addition, a wall-mount subwoofer ESUB-6W/SW ensures a dynamic and well-balanced bass reproduction. Power is supplied via 2 x mono power amplifier PA-912S (1 x 120 W). Flush-mount ceiling speakers EDL-16 and 2-way speaker systems WALL-06T/SW deliver unobtrusive and pleasant background music to changing rooms and hallways. A mono power amplifier PA-924S (1 x 240 W) and a mono mixing amplifier PA-306 (1 x 60 W) provide sufficient power. The sound system is controlled via easy-to-use 4-zone mixer PA-6040MPX which is connected ahead of the PA power amplifier and allows for connection of one or multiple microphone stations. The sound level is automatically lowered when announcements are made.

Products for this scenario:



PAB-6WP/WS

Order No. 0253560 Weatherproof high-performance PA speaker system. 100 W



EDL-16

Order No. 0163820 PA ceiling speaker



WALL-06T/SW

Order No. 0163600

Pair of 2-way PA speaker systems



WALL-05T/SW

Order No. 0163580

Pair of 2-way PA speaker systems



ESUB-6W/SW

Order No. 0259920 Wall-mount PA subwoofer, 2 x 60 W



PA-912S

Order No. 0177000

Mono PA power amplifier, 120 W



PA-924S

Order No. 0177010

Mono PA power amplifier, 240 W



PA-306

Order No. 0176800 Mono PA mixing amplifier



PA-1960

Order No. 0172550

High-power mono PA amplifier



PA-6040MPX

Order No. 0174760 4-zone mixer



PA 4-zone paging desktop microphone



CD-112/BT


Order No. 0212940

CD and MP3 player with Bluetooth receiver, USB interface and SD/MMC card slot



Trampoline Park

Flush-mount speakers and surface-mount speakers



Zone 1

Zone 2

Zone 3

Zone 4

Dental Practice

Flush-mount speakers and surface-mount speakers 150-280 m²

Customer requirements:

- Excellent sound characteristics for reproduction of music and speech
- Unobtrusive music reproduction for a pleasant ambience in the treatment rooms
- Volume control per channel for individual adjustment in each room
- Microphone station at the reception desk for calling in patients and for general announcements in the waiting area and treatment rooms

Solution

Unobtrusive wall speakers ESP-157/WS are used to ensure a pleasant sound in the treatment rooms. The 2-way system provides a great sound for reproduction of both speech and music. Flush-mount speakers EDL-10TW/WS which have been installed in the hallway and waiting area allow for a continuous PA application in the entire practice. The class D amplifier PA-1450D provides 4 x 50 W. With the mixer PA-6040MPX, it is possible to implement a multi-room application with an individual control of up to four zones. Thus, it is possible for practice staff to direct announcements to one specific room or to a group of zones. The audio player CD-112/BT also provides unobtrusive background music to either one zone or several zones.

Products for this scenario:



ESP-157/WS

Order No. 0163210 PA wall speaker



EDL-10TW/WS

Order No. 0163380

PA ceiling speaker with integrated tweeter



PA-1450D Order No. 0172950 4-channel class D PA amplifier



PA-6040MPX Order No. 0174760

4-zone mixer



CD-112/BT

Order No. 0212940

CD and MP3 player with Bluetooth receiver, USB interface and SD/MMC card slot



PA-4000RC Order No. 0236010

PA 4-zone paging desktop microphone


ATT-536PEU Order No. 0173920

Wall-mounted PA volume control



Dental Practice

Flush-mount speakers and surface-mount speakers 150-280 m²













Retirement Home

Flush-mount speakers 500–700 m²

Customer requirements:

- Reliable audio system for a PA application with 2 speaker zones in the common rooms
- Amplifier system with tone control, connection facility for a wireless microphone system including inductive transmission via loop
- Music reproduction of CD, MP3, external storage media as well as radio reception and Bluetooth reception
- User-defined routing of all input channels to both of the speaker zones

Solution

Furnishing and equipment in a retirement home have to be perfectly matched to the needs of residents and staff. Reliability, convenience and barrier-free access are essential for the elderly and people in need of care. A universal PA system is used for regular in-house or public events such as exhibitions, concerts and lectures. Ceiling speakers EDL-116TW with 2-way coaxial speakers (6") have been installed in the common rooms and living room and always provide an excellent reproduction of speech and music for most varying types of events. Two mono power amplifiers PA-900S with 1 x 120 W each provide sufficient power for the connected speaker lines. The loop system which is driven by 2 active loop amplifiers LA-202 ensures barrier-free access to each event. Zone mixer PA-4040MPX is the central interface of the system where all the signals are routed and then distributed. It provides user-defined routing of all input channels to both of the zones. The input signals include a 16-channel mono PLL audio transmission system TXA-802SR or TXA-800HT. The connected audio player CD-112RDS/BT is used for music reproductions. USB storage media, SDHC cards and audio sources like CD, MP3, FM RDS tuner or Bluetooth media are also part of the remarkable variety of playback options.

Products for this scenario:



EDL-116TW Order No. 0163840

PA ceiling speaker



Order No. 0172080 Mono PA power amplifier



PA-4040MPX Order No. 0173450 4-zone mixer



LA-202 Order No. 0176360 Active loop amplifier



Order No. 0212950 CD and MP3 player with FM RDS tuner and Bluetooth receiver



Order No. 0172990 2-channel multifrequency receiver



64

Retirement Home

Flush-mount speakers 500-700 m²







Zone 1

Sports and Leisure Centre

Flush-mount speakers and surface-mount speakers 1,600-1,900 m²

Customer requirements:

- PA system with flexible configuration for different functional areas, including lobby, bistro, indoor sports facilities and spa area
- High-quality multi-zone solution, each zone to be provided with different playlists and with an individual volume level
- Unobtrusive background music in the lobby, swimming pool area and adjoining changing rooms as well as sanitary facilities
- PA speaker systems with a high sound pressure and a powerful sound for multifunctional sports fields
- Robust flush-mount ceiling speakers for the sauna and pool area
- Microphone station at the reception desk for making announcements

Solution

Depending on the area of application, highest speech intelligibility, unobtrusive background music or a powerful sound are required.

At the reception, an installed shuttle PC with music software is used as an audio source to direct specific recordings to the speaker lines. In addition, important announcements can be made via the connected gooseneck microphone ECM-300DT.

In the lobby and adjoining bistro area, active 2-way flush-mount ceiling speakers EDL-80DT provide pleasant background music and are complemented by DSP-controlled wall speakers WALL-05DT which have also been applied here.

In the spa area, ceiling speakers EDL-156 provide unobtrusive background music. The Dante® instreamers PA-900DT and AKB-160DT convert digital audio signals into an analogue signal which is amplified and then streamed. On the multifunctional sports field, professional PA speaker systems MOVE-08 which are integrated via a Dante®-enabled breakout box DSM-48DT provide a powerful sound. On the other sports fields, a well-balanced sound is ensured by combining ball-proof wall speakers ESP-72/WS and amplifier module AKB-160DT.

Additional flush-mount speakers and surface-mount speakers have been used in the changing rooms, sanitary facilities as well as in the shower area for a comprehensive and homogeneous sound distribution throughout the whole leisure centre.

Products for this scenario:



WALL-05DT Order No. 0132390

Active speaker with integrated Dante® module



EDL-80DT Order No. 0163480

Active 2-way flush-mount ceiling speaker with integrated Dante® module



ETS-630DT

Order No. 0163490 Active PA column speaker with

integrated Dante® module



EDL-156

Order No. 0161910 Weatherproof PA ceiling speaker



EDL-10TW/WS

Order No. 0163380

PA ceiling speaker with integrated tweeter



ESP-72/WS

Order No. 0162130 PA wall speaker



MOVE-08

Order No. 0254900 Professional PA speaker system, 200 W, 8 Ω



PA-900DT

Order No. 0176080

Mono PA mixing amplifier with integrated Dante® module



PA-4240

Order No. 0170820 PA power amplifier



AKB-160DT Order No. 0176070

PA amplifier module with integrated Dante® module



BMS-ZONE3

Order No. 0176180

Shuttle computer with ROSI BMS software, 3 channels, 1,950 tracks, including Dante® Virtual Soundcard licence



DSM-48DT

Order No. 0257790 Digital speaker management system with Dante® module

Order No. 0236910

PA desktop microphone with integrated Dante® module



DTTA-2

Order No. 0257890 Dante® I/O box



Sports and Leisure Centre

Flush-mount speakers and surface-mount speakers



Are you planning a similar PA application? We accept the challenge and will find the perfect solution for your project. Just contact us.





Zone 1

Zone 2

Zone 3

Zone 4





Solutions for Restaurants + Bars and the Hotel Sector

Bar

Flush-mount speakers and surface-mount speakers 150–270 m²

Customer requirements:

- Flexible mutli-zone control for individual music reproductions in the four zones
- Unobtrusive background music for the lounge area which should not disrupt ongoing conversations and also allows you to order drinks at the bar without any problems
- Bass-heavy music of higher volume levels on the dance floor
- Unobtrusive background music for the bar and sanitary facilities
- Music reproduction from CD, MP3 file or USB storage medium
- Connection facility for various external audio sources such as tablet PC, smartphone and laptop



Solution

In addition to unobtrusive and decentral background music for the bar and lounge area as well as for the sanitary facilities, the system must also ensure a powerful sound with a high level stability on the dance floor. In order to ensure a suitable PA application for each individual zone, we have implemented a multi-room solution with a total of 4 zones. Speakers EUL-60/SW radiate pleasant background music to the bar and lounge area which still allows you to hold a conversation. For the sanitary facilities, we have used ceiling speakers EDL-82HQ to provide quiet background music without appearing dominant or obtrusive. The speakers PAB-308/SW and a subwoofer PSUB-12AKA ensure a lively ambience on the dance floor. Each of the speaker series is driven by the matrix mixing amplifier PA-12040 with 4 x 120 W. The connected audio player CD-122 is able to replay CDs as well as MP3 files from USB storage media or SD cards.

Products for this scenario:



EUL-60/SWOrder No. 0161170
Pair of universal PA speaker systems



EDL-82HQ Order No. 0163440 PA hi-fi wall and ceiling speaker



PAB-308/SW Order No. 0254290 Universal PA speaker system, 125 W



Active 2.1 PA subwoofer, 1,200 W

PA-12040 Order No. 0173390

4-zone matrix mixing amplifier



Order No. 0212820

Dual CD and MP3 player with USB 2.0 interface and SD/MMC card slot



ATT-235H/WS Order No. 0176130

Wall-mounted PA volume control



Zone 1

Zone 2

Zone 3

Zone 4

Restaurant

Flush-mount speakers and surface-mount speakers 140–250 m²

Customer requirements:

- Flexible multi-zone volume control in the guest area, outdoor area and in the sanitary facilities
- Well-balanced sound for unobtrusive background music in the different sound zones
- Unobtrusive integration of the speakers into the guest area
- Weatherproof outdoor speakers with excellent sound characteristics
- Versatile reproduction options from CD, MP3 file and Internet radio
- Streaming media via network and wireless audio transmission via Bluetooth

Solution

A flexible multi-zone PA application provides pleasant and unobtrusive music in the entire restaurant. Flush-mount ceiling speakers EDL-10TW/WS can unobtrusively be integrated into the restaurant's environment. The 20 cm (8") 2-way coaxial speaker with additional tweeter ensure an excellent sound quality of the music played with a consistent radiation pattern. The remaining areas are provided with pleasant background music, too. For the outdoor area, we have applied weatherproof speaker systems ESP-232/WS with IP55 certification and for the sanitary facilities, we have installed ceiling speakers EDL-155. The mixer MPX-4PA distributes signals to all three zones with user-defined routing of all input channels. A 4-channel class D PA amplifier PA-1450D provides the connected speakers with a nominal power of 200 W. Various audio sources can be fed into the system via the two audio players. Audio player WAP-200 is suitable for reception of the digital radio DAB+ and allows access to more than 20,000 Internet radio stations worldwide. In addition, it allows for streaming media files which can be accessed via the network (UPnP server). For wireless audio reproduction, the CD player CD-112/BT features an integrated Bluetooth receiver for quick and easy access to a laptop, smartphone or tablet PC.

Products for this scenario:



EDL-10TW/WS

Order No. 0163380

PA ceiling speaker with integrated tweeter



2 X

EDL-155 Order No. 0162920 PA ceiling speaker



2 x

ESP-232/WS Order No. 0162610

Weatherproof 2-way PA wall-mount speaker system



PA-1450D

Order No. 0172950 4-channel class D PA amplifier



I X

MPX-4PA Order No. 0202070

3-zone mixer



1 x

CD-112/BT Order No. 0212940

CD and MP3 player with Bluetooth receiver, USB interface and SD/MMC card slot



1 >

WAP-200 Order No. 0387030

Internet radio, FM RDS and DAB+ tuner, MP3 player



Restaurant

Flush-mount speakers and surface-mount speakers 140–250 m²



Zone 1





Function Room

Surface-mount speakers 150–340 m²

Customer requirements:

- Flexible solution for versatile PA applications
- Efficient speakers to provide a powerful sound with an excellent sound quality
- Music reproduction from CD, MP3 or wireless via a laptop with integrated Bluetooth module
- Connection facility for one or several (wireless) microphones



Solution

PA speaker systems EUL-2/SW provide a well-balanced and dynamic sound and thus, allow for versatile reproductions of music and speech. Two subwoofers EUL-2SUB/SW provide a low and dynamic bass reproduction. Speaker systems and subwoofer are driven by a power amplifier PA-2240 with 2 x 240 W. A preamplifier PA-1414MX is connected in front of the power amplifier which provides versatile connection facilities and feeds the input channel to either one channel or two channels. A CD and MP3 player is used as an audio source and provides most versatile reproduction options: the CD-112RDS/BT with integrated FM RDS tuner allows for reproduction from USB storage media and SD/MMC cards as well as wireless music reproduction via Bluetooth. In addition, it is also possible to connect a microphone signal to the preamplifier, if required.

Products for this scenario:



EUL-2/SW Order No. 0174450 PA speaker system





Order No. 0174770 10-channel PA preamplifier



1 X
CD-112RDS/BT
Order No. 0212950

CD and MP3 player with FM RDS tuner and Bluetooth receiver



Order No. 0172990 2-channel multifrequency receiver



Function Room

Surface-mount speakers 150–340 m²



Café

Flush-mount speakers 90–150 m²

Customer requirements:

- High-quality music reproduction with a homogeneous sound distribution in the room
- Simple and intuitive operation of the applied PA technology, even for untrained or inexperienced users
- Various audio sources for music reproduction, including MP3 player with USB/SD interface, FM radio or via Bluetooth-enabled devices
- Flexible connection facilities for additional music sources



Movable PA ceiling speakers EDL-65TW feature a well-balanced sound and can unobtrusively be integrated into the guest area of the café. The high-quality 2-way coaxial system with 2-way crossover network provides unobtrusive background music with excellent sound characteristics. In the sanitary facilities, we have used 2 x EDL-22/WS which can separately be controlled via volume control ATT-524PEU. The PA ceiling speakers are of a compact design, but still provide a very wide-band music reproduction. A class D mixing amplifier PA-812DMP provides sufficient power with 120 W per channel for the connected speaker series and ensures a high-quality audio reproduction with low heat generation. The range of features also includes various sound adjustments, versatile connection facilities and various integrated media functions. In addition to the integrated MP3 player and FM tuner, music sources can be played via Bluetooth connection, too. It is also possible to connect microphones or additional audio devices to the PA-812DMP.

Products for this scenario:

2 x

EDL-65TW Order No. 0162220

Movable PA ceiling speaker



2 x

EDL-22/WS

Order No. 0162770 PA ceiling speaker



1 x

PA-812DMP Order No. 0176930

Mono class D PA mixing amplifier with integrated MP3 player, FM tuner and

Bluetooth





ATT-524PEU Order No. 0173910

Wall-mounted PA volume control with 24 V emergency priority relay



Café

Flush-mount speakers 90–150 m²



Food Truck

Surface-mount speakers 10–15 m²

Customer requirements:

- Weatherproof and robust outdoor speaker systems for high-quality music reproduction
- Flexible installation of the applied speaker technology
- Simple operation and easy installation of the complete audio system
- MP3 player with USB interface and SDHC card slot for music reproduction
- Reliable amplifier technology for mobile applications via 12 V battery operation
- Optional: to make announcements via microphone and distribute them to both of the speakers



Solution

A new food culture conquers the world: food trucks are becoming increasingly popular and provide us with juicy burgers, spicy burritos or crispy tacos on festivals, at events or street parties. Listening to music or a radio programme is not only a pleasant distraction for customers waiting in line. Nowadays, the comprehensive catering concept of food truck owners more and more includes suitable music. PA systems for 4-wheeled street food catering have to meet very complex requirements of mobile applications. Robust, weatherproof speaker systems ESP-215/WS, which are suitable for outdoor applications, provide the appropriate high-quality sound for guests. The 2-way systems are supplied with stainless steel mounting brackets and can be flexibly aligned to the required area. The mono mixing amplifier PA-803USB with a power rating of 1 x 30 W is used as power amplifier. The system is particularly suitable for mobile applications, thanks to the fanless cooling concept, the compact size and the uncomplicated operation via a 12 V power supply. An integrated MP3 player can be used for music reproduction via USB interface or SDHC card slot. Additional connections for microphones, external CD players or FM RDS and DAB+ tuners are also available.

Products for this scenario:

2 x

ESP-215/WS

Order No. 0199990 Weatherproof PA speaker system



1 x

PA-803USB

Order No. 0174650

Mono PA mixing amplifier with integrated MP3 player



1 x

PDM-300 Order No. 0231200

PA desktop microphone



Food Truck

Surface-mount speakers 10-15 m²



Hotel Room

Flush-mount speakers 15–25 m²

Customer requirements:

- Excellent sound characteristics
- Unobtrusive integration of flush-mount ceiling speakers into a hotel room
- Music reproduction via streaming apps of the hotel guests
- Simple and intuitive operation, even for inexperienced users
- Bluetooth connection with smartphone or tablet



Solution

It becomes more and more important for hotels to keep the standards of the services offered or even improve them. Nowadays, access to WLAN is a standard service offered to the guests but Bluetooth-compatible audio systems which allow you to stream music via mobile devices are rarely available. The Bluetooth-enabled amplifier module IWA-05BT/WS is a convenient and easy-to-use solution for hotel rooms. The audio receiver features a user-friendly control unit and is integrated directly into the wall. Thanks to its compact design, it can be mounted into standard installation boxes from Ø 45 mm on. The gain level and thus the maximum volume level possible can be preset, if required. For the music reproduction from Bluetooth-enabled devices, the flush-mounted amplifier is connected to 2 passive ceiling speakers EDL-42HQ. The 2-way version with coaxial dome tweeter, 10 cm (4") bass speaker with waveguide and 20 mm (3/4") silk tweeter provides a well-balanced sound to every corner of the hotel room. Thus, hotel guests can enjoy their favourite songs or streaming apps.

Products for this scenario:

2 x

EDL-42HQ

Order No. 0163890 Hi-fi wall and ceiling speaker, 15 W



1 x

IWA-05BT/WS

Order No. 0179000

Flush-mounted module with Bluetooth audio receiver/amplifier



Hotel Room

Flush-mount speakers 15–25 m²







Solutions for Office Buildings and Conference Rooms

Flush-mount speakers 250-500 m²

Customer requirements:

- Unobtrusive flush-mount ceiling speakers for reproduction of music and speech
- Pleasant background music with individual volume control for each office
- Announcements made via microphone stations at the reception to have priority and briefly interrupt the background music
- Music reproduction of radio, CD and USB storage media
- Speakers in the conference room with excellent sound characteristics for multifunctional use, e.g. for lectures and presentations



Solution

Unobtrusive flush-mount ceiling speakers EDL-10TW/WS combine an excellent sound quality with highest speech intelligibility. Wall-mounted PA volume controls allow for an individual volume control of the background music in the offices. We have also installed 4 speakers EDL-620 in the treatment rooms. Both speaker series are driven by the high-performance power amplifier PA-6240. A CD module PA-1140RCD for the front insertion compartment of the amplifier is used as an audio source which allows for a music reproduction from radio, CD or a USB storage medium. When making announcements at the reception via the microphone station PA-6000RC, all other audio channels are muted thanks to the adjustable priority function.

Products for this scenario:



EDL-10TW/WS

Order No. 0163380 PA ceiling speaker with integrated tweeter



EDL-620

Order No. 0162590

PA ceiling speaker

PA-6240

Order No. 0172180

6-zone mono PA mixing amplifier



PA-1140RCD

Order No. 0173530

RDS tuner/CD player insertion with USB interface





PA zone paging desktop microphone

ATT-512PEU

Order No. 0173900

Wall-mounted PA volume control



Flush-mount speakers 250–500 m²















Zone 4

Surface-mount speakers 250-500 m²

Customer requirements:

- Compact, yet top-quality wall speakers for high-quality background music
- Music reproduction from CD, MP3 files, radio or external storage media
- Excellent sound quality of the speakers in the treatment rooms
- User-friendly and intuitive operation for the user

Solution

PA speaker systems EUL-60/SW are used for the PA application in a conference room and office building. Compact wall-mount speakers ESP-232/WS provide an excellent sound in the corridors. Both speaker series are connected to the amplifier PA-12040 which provides a total output of 4 x 120 W. Thus, it is possible to distribute the connected speakers to up to 4 speaker zones and allow for an individual volume control. For an audio player, we used a CD-112RDS/BT which features an integrated FM RDS tuner and Bluetooth receiver as well as a CD and MP3 function.

Products for this scenario:

4 x

EUL-60/WS

Order No. 0161180
Pair of universal PA speaker systems



3 x

ESP-232/WS

Order No. 0162610

Weatherproof 2-way PA wall-mount speaker system



1 x

PA-12040

Order No. 0173390

4-zone matrix mixing amplifier





CD-112RDS/BT

Order No. 0212950

CD and MP3 player with FM RDS tuner and Bluetooth receiver



Surface-mount speakers 250-500 m²



Zone 1







Zone 4

Seminar Room

Flush-mount speakers 80–150 m²

Customer requirements:

- Unobtrusive flush-mount ceiling speakers with excellent sound characteristics
- Excellent sound quality and speech intelligibility at every seating position in the room
- Bluetooth support for laptops, smartphones or tablet PCs
- Optional: connection of one or several wireless microphones for presenters and lecture halls



Solution

Flush-mount ceiling speakers EDL-82HQ feature a stylish flush fit housing and thus are perfectly suitable for an unobtrusive integration into the existing environment. Combined with the 240 W mixing amplifier, the connected speakers with excellent sound characteristics provide an impressive performance. The audio player CD-112/BT is used as a signal source and is able to playback MP3 files from USB storage media and SD/MMC memory cards as well as allow for wireless transmission via Bluetooth.

Products for this scenario:

6 x

EDL-82HQ Order No. 0163440

PA hi-fi wall and ceiling speaker



1 x

PA-324

Order No. 0174420 Mono PA mixing amplifier



1 x

CD-112/BT

Order No. 0212940

CD and MP3 player with Bluetooth receiver, USB interface and SD/MMC card slot





Seminar Room

Surface-mount speakers 80–150 m²

Customer requirements:

- 2-zone control for front speakers and decentral wall speakers
- Audio reproduction from CDs, MP3 files, USB storage media, SD/MMC cards or wireless from external devices, e.g. laptop and smartphone
- Excellent speech intelligibility in the entire room
- Connection facility of one or several wireless microphones

Solution

The particularly slim line array speakers ETS-120SL/WS have been applied as front speakers. The high-performance design speakers impress by an unobtrusive and elegant design, yet feature an excellent sound quality. The applied mono mixing amplifier PA-4040 provides extensive connection facilities and easily meets the requirements of multi-zone applications. Thanks to the CD and MP3 player CD-112/BT which features a Bluetooth receiver, SD/MMC card slot and USB interface, it is possible to provide music reproductions from most varying audio sources.

Products for this scenario:

1 x

ETS-120SL/WS

Order No. 0163450
Pair of line array design speakers in slimline extruded aluminium cabinets



EUL-30/WS

Order No. 0161160

Pair of universal PA speaker systems



TXA-802SR

Order No. 0172990

2-channel multifrequency receiver



TXA-800HT

Order No. 0172260

Hand-held microphone with integrated multifrequency transmitter



PA-4040

Order No. 0172520

4-zone matrix mixing amplifier






CD-112/BT Order No. 0212940

CD and MP3 player with Bluetooth receiver, USB interface and SD/MMC card slot





Conference Room

Surface-mount speakers 60–80 m²

Customer requirements:

- DSP-controlled active speaker systems for wall mounting and ceiling suspension with PoE (Power over Ethernet) which provide a powerful sound, e.g. for sound reproduction from a PC
- Connected speakers to provide a homogeneous sound distribution for an excellent speech intelligibility at every seating position in the room
- Connecting facility for a tie clip microphone and a lectern microphone for most versatile PA applications, e.g. for meetings, workshops, conventions or conferences
- Easiest operation and maximum flexibility, e.g. for PC presentations or reproduction of media via a stationary PC or laptop

Solution

Conference rooms should be suitable for most versatile applications and remain user-friendly. The key requirements for this are an excellent speech intelligibility and a top-quality media reproduction. Four Dante®-enabled wall speakers WALL-05DT have been installed and allow for an excellent audio quality. The active sound system is suitable for intuitive operation and achieves a homogeneous sound radiation. Thus, you can ensure a well-balanced sound radiation at every listening position in the room. In addition, pocket transmitter TXA-800HSE with headband microphone or tie clip microphone has been applied to ensure the speaker's mobility, e.g. at lectures or presentations. The presentation of multimedia stereo signal sources or stereo contents via a connected laptop is as easy as child's play: the laptop signal is fed-into the speaker system via the audio signal crossover network HDAW-203 using HDMI™. HDAW-203 is extracting the stereo audio signal from the video signal which is then converted into 2 x mono using the converter SMC-1. The mono signal is then transmitted to 4 active speakers WALL-05DT via the Dante® output (EtherCon/RJ45) of the mini stage box DTTA-2. The Dante[®] I/O box is provided with power via PoE or via an optional power supply.

Products for this scenario:



WALL-05DT

Order No. 0132390

Active speaker with integrated Dante® module



1 x

TXA-802SR Order No. 0172990

2-channel multifrequency receiver





TXA-800HSE Order No. 0172250

Multifrequency pocket transmitter



1 x

DTTA-2 Order No. 0257890 Dante[®] I/O box





HDAW-203 Order No. 0189600

HDMI™ audio signal splitter



1 x

Order No. 0211930 Stereo/mono converter



Conference Room

Surface-mount speakers 60-80 m²





Your Project is Our Project

Profound planning results in an excellent sound and highest speech intelligibility


A genuine reproduction, perfect speech intelligibility and an optimum sound are crucial for a successful PA project. The requirements made on acoustics and sound have, however, increased considerably in recent years. Thus, thorough planning for your individual project is indispensable, with each project having a special focus and specific requirements. The challenge is to precisely match the large number of technical details and components:

When selecting suitable speakers, a natural and genuine sound quality for the reproduction of speech and music is top of the list. In classrooms, conference rooms, lecture rooms, seminar rooms or in houses of worship, excellent speech intelligibility is required both in the first and last row. However, requirements for restaurants, shops or cafés are totally different where we want pleasant and unobtrusive background music to ensure an appealing environment; this triggers positive emotions and invites you to linger. The alignment of the speakers should achieve a consistent radiation pattern. Radiation angle, frequency range and sound pressure are just a few speaker parameters which influence the reproduction of speech and music.

For each PA project, we have to consider specific acoustic surroundings when creating the perfect PA solution. Interfering reflections, acoustic feedback or echoes must be prevented and the announcements should be heard and understood at every position, even with high background noise.

Planning a professional PA system requires comprehensive know-how and careful project development. Speakers, amplifiers, audio players, microphone systems, mixers, hundreds of metres of cable, distributors and plugs - everything has to be matched down to the smallest detail. Right from the start, planning experts from MONACOR will be at your side to support you so you can keep track of your PA project. Because: Your Project is Our Project.





Your Project is Our Project

Each project starts with a series of questions. Together, we will certainly find the right answers to your questions and in close cooperation are able to create an individual PA concept. Each concept results from the requirements you make and respective local conditions. Together with planning experts from MONACOR, you will be able to create the perfect solution for your intended location.

- Where do you want to install the PA system? Indoor or outdoor solution
- What is the intended use of the PA system? Focus to be placed on speech intelligibility or background music
- What is the location like? e.g. surface materials (glass, concrete or carpet) and ceiling structure. The possibility of mounting flush-mount speakers into a (suspended) ceiling has to be checked individually
- How big is the area to be covered by the PA application? e.g. floor area and ceiling height
- How many people does the PA system have to reach?
- What kind of audio sources are to be used for the reproduction?
- Do you need connections for microphones (wireless or wired)?
- And do not forget: what kind of a budget is available?

A dimensioned drawing or room measurements complete the profile of requirements. Considering all of the objectives, we can make sure that the PA system will meet your requirements and is going to be suitable for the intended use.


Success can be Planned

MONACOR and its staff continuously implement an extensive service and thus stand out from the rest. We always consider the latest trends and proceed with efficiency and reliability. We love to see quality in both our products and our business relationships. With every project, we therefore rely on a close and trusting working relationship with our partners — right from the planning stage through to the final inspection, including the implementation.

This is what you can expect from us:

- Comprehensive support during the planning stage for various types of use and fields of applications
- Full analysis of expectations as well as spatial conditions and acoustic conditions
- Tailor-made PA concepts which are perfectly adapted to the environment and your requirements
- Comprehensive know-how and years of experience from numerous successfully implemented PA projects
- Careful selection of suitable system components according to special room requirements for ensuring a top-quality sound and/or speech intelligibility
- Close cooperation and coordination with planners, architects and expert installers
- Maximum planning reliability: 3-year warranty on products from MONACOR

Use our experience, our expertise and our competence to ensure your project to be a success.



Our Technical Project Management: Expert Knowledge for a Successful Project

No two projects are the same: reproductions of speech and/or music have to meet most varying requirements as well adapt to different room acoustics which all have to be considered when planning a PA system.

Our planning experts from the Technical Project Management will assist you in searching for the perfect audio solution for your project, right from the planning stage through to the final inspection. Thus, we are able to identify challenges at an early stage and together form the basis for a successful project.

Our key account managers travel all over Germany and Austria in order to create a tailor-made solution with you. The colleagues on site will make your project our project.

With this brochure, we cannot of course publish the whole range of PA solutions. However, our project specialists will be happy to discuss your project in a personal meeting. We will be happy to implement your project and look forward to your challenge.



Frank Kammer TPM Manager Audio and Security

kammer@monacor.de +49 421 4865 360



Jürgen Eggeling Key Account Manager

eggeling@monacor.de +49 152 34037935



Christian Meyer Technical Project Management Audio and Light

c.meyer@monacor.de +49 421 4865 351



Michael Dreis Key Account Manager

dreis@monacor.de +49 152 33871536



Michael Krebbing Technical Project Management Audio and Security

krebbing@monacor.de +49 421 4865 352




Mustapha Idrissi Key Account Manager

idrissi@monacor.de +49 152 32093851



Michael Friedsam Key Account Manager

friedsam@monacor.de +49 173 8311187



E-mail: projekte@monacor.de

Central telephone number: +49 421 4865 355

Central fax number: +49 421 4865 356

© Photographs

stock.adobe.com: Jürgen Fälchle — "Empfangstheke und Flur", page 3. Zsolnai Gergely — "Dental Chair IV.", page 3. Zsolnai Gergely — "Dental Chair IV.", page 3. Zsolnai Gergely — "Modern Dental Romm Ill.", page 3. Photowahn — "Moderner Zahnarztstuhl mit Wartezimmer im Hintergrund", page 3. Roman — "Conference Room with a view", page 4. zhu difeng — "fashion clothes shopfront in shopping mall", page 4. Dmitry Vereshchagin — "Interior of a sport hall for soccer or handball", page 4. zhu difeng — "modern clothes retail shop in shopping mall", page 10. thaiview — "Supermarket, fruit and vegetable zone", page 12. 06photo — "Large furniture warehouse", page 14. Joshhh — "Mannequins with check pattern short and long sleeve shirts in st', page 18. Kwangmoo — "Gas station with sun light", page 24. WavebreakMediaMicro — "Hairdresser equipment in salon", page 26. Tomasz Zajda — "Automotive Car Business", page 28. chaoss — "big empty modern lecture hall", page 32. Robert Elias — "school hallway", page 34. smgoloviznin — "empty classroom and blackboard", page 36. davidsonlentz — "Lecture Hall", page 38. smgoloviznin — "empty classroom and blackboard", page 36. davidsonlentz — "Modern gym interior with equipment, fitness exercise bikes", page 44. oben901 — "多摩川河川敷のグラウンド" , page 46. poyre — "Campsite", page 48. LiliGraphie — "Vintage typewriter golden frame old office accessories", page 50. David Biagi — "Dinosaur Bones", page 52. mRGB — "Empty indoor riding hall", page 54. Dmitry Vereshchagin — "banisters in a swimming pool", page 56. zhu difeng — "apparatus and equipment in modern gym", page 62. izikmd — "Beautiful sunset over the lake. Public park in Raison Bois-franc in Montreal, Canada.", page 64. tanothai — "blurred badminton shuttlecock and racket on court", page 66. YakobchukOlena — "Modern public place with stylish interior", page 68. ivylingpy — "Lounge and pub", page 70. Photographee.eu — "Spacious modern restaurant", page 71. Lensife — "Festsaal II", page 74. devteev — "Bakery interior", page 66. Nove in the cour

Fotolia: WavebreakmediaMicro - "Shadowing a smiling businessman", page 7. fiphoto - "modern and fashion clothes store", page 16. tang90246 - "Mannequins in fashionable dresses", page 20. amst - "Boutique", page 22. a2l - "modern wooden conference room with tables an chairs", page 88.



HEADQUARTERS MONACOR INTERNATIONAL

Zum Falsch 36 28307 Bremen Germany

Tel.: +49 421 4865-0 Fax: +49 421 488415 info@monacor.com

www.monacor-international.com

4 007754 274677

CAS 2020 K20-196SODEEN Order No. 1000035 K-1138.02.01.01.2020



MONACOR and IMG STAGELINE are brands of the company group MONACOR INTERNATIONAL.

